



LC90W350-700

Constant Current Driver

Model: LC90W350-700



Model	Output Current	Input Current	Input Power	Output Power Range	PF	Efficiency	Output Voltage	No load Voltage
LC90W350-700	350mA	0.6A	105W	59.85-89.95W	0.95	90%	171-257V	300V
	500mA			60-90W			120-180V	
	700mA			59.5-90.3W			85-129V	

* Test result @230V, 50Hz, Full Load.


1. Parameters

category	Item	Technical Norm
Features	Output Type	Constant Current
	Output Features	Non-Isolation
	IP Grade	IP20
	Insulation Class	Class I
Input	Rated Input Voltage	220-240VAC
	Range of Input Voltage	176-264VAC
	Range of DC Input Voltage	176-280VDC
	Frequency	50/60Hz
	Input Current	≤0.6A
	Input Power	≤105W
	Power Factor	≥0.95 (230VAC, full load)
	THD	≤15% (230VAC, full load)
	No-load Power Consumption	≤0.5W @230VAC
	Inrush Current	≤60A/100us (230VAC, full load)
	Connected quantity of 16A Breaker	8pcs/type B ;13pcs/type C
Output	Output Voltage	171-257V 120-180V 85-129V
	No Load Voltage	300VDC Max.
	Output Current	350mA -500mA-700mA
	Max. Output Power	90W
	Efficiency	≥90%
	Current Ripple	±3% (Imax-Imin) / (Imax+Imin)
	Current Accuracy	±5%
	Start up Time	≤0.5S (230VAC, full load)
Protection	Input Over Voltage Protection	Input voltage>380Vac,Driver will stop working and


KGP Electronics GmbH
Hueckstraße 19
DE-58511 Lüdenscheid

KGP-V0.02

3. Dimension (Unit: mm)




4. Block Diagram



5. Packing information

Carton L*W*H(mm)	Pcs/Carton	Net weight/ Pcs(kg)	Net weight/ Carton(kg)	Gross weight / Carton(kg)
410*270*190	60	0.23	13.8	14.36

6. Wiring Diagram



7. Wiring instructions

- All connections must be kept as short as possible to ensure good EMI behaviour
- Mains leads should be kept apart from LED Driver and other leads (ideally 5 – 10 cm distance)
- Advice the maximum length of output wires is 3 m
- Secondary switching is not permitted (Except for constant voltage)
- Incorrect wiring can damage LED modules.
- The wiring must be protected against short circuits to earth (sharp edged metals parts, metal cable clips, louver, etc.)

Fig. A:LC90W350-700